



Cost Effective Auto Tracking PTZ Cameras




Dimensions




In-Ceiling Mount



Wall Mount



Pole Mount



Surface Mount

Features

- ※ Auto search & track on moving object, with adjustable precision & tracking state;
- ※ Auto return to home position/preset and keep tracking after a programmable interval when object gets out of adjustable target area;
- ※ Tracking during cruising;
- ※ English OSD menu(with password protection) to display and program camera;
- ※ Auto actions(such as tracking, preset,cruise, pattern scan etc.)on power on, alarm, park;
- ※ Camera address programmable via OSD menu;
- ※ Programmable zone title, preset, and camera title;
- ※ P/T speed adjustable as per the zoom times;
- ※ Alarm input and relay output;
- ※ Multi-protocols supported with adjustable baud rate;
- ※ Auto/Manual adjustments of IRIS, BLC, FOCUS and WB;
- ※ Auto/Manual start of heating device.

Specification

Model WS-TS1805

Camera

Image Sensor 1/3" SONY Exview HAD CCD II

Effective Pixels PAL:960(H) x 582(V)/NTSC:967(H) x 494(V)

Resolution 650TVL

Sync. System Internal

Video Output CVBS(1Vp-p75Ω)

Min.Illumination 0.01Lux

WB Auto / Indoor / Outdoor / Manual

Focal Auto / Manual

Exposure Control Auto / Manual

S/N Ratio ≥48dB

BLC Yes

WDR D-WDR

DNR 2D/OFF

Day/Night Mode Color/B/W/Auto

Lens

Optical Zoom 18X

Focal f=5mm-9.0mm

IRIS Control F1.6-F3.0

Field of View H:52.5°(w) - 3.0°(T); V: 40.0°(W) - 2.3°(T)

General

Function Motion Tracking

Mounting Type Surface,wall, Pole,In-ceiling, Wall with Power box

AGC Auto/Manual

BLC Open/Close

Pan/Tilt Speed Pan:0.05°/s~220°/s; Tilt:0.03°/s~140°/s

Pan/Tilt Range Pan:0°~360° continuous; Tilt: 0° ~ 90° Auto Flip

Auto Cruise Auto switch from 1 to 30 preset positions sequentlally

Pattern Scan 4 Routes

Preset Number 256

Spectra Address 0 ~ 255

Control Interface RS-485

Protocol Pelco-P/Pelco-D

Baud Rate 1200/2400/4800/9600/19200bps

Zones 8 zones

Alarms 4 Inputs, 2 Outputs

Working Temperature -25°C - 70°C(w/o heater), -50°C - 70°C(with heater)

Power Supply DC12V / DC24V /AC 24V

※※※Product specification are subject to change without notice ※※※

www.winsafecctv.com