MULTI Protocols Keyboard Controller(WS-M120B/130B)

- Set the address range of the MS series camera and decoder:0-255
- Operate the pan/tilt of speed dome camera to move in different speed level
- ※Initial setting are subjuect to change through the speed dome camera menu
- Manually control the Focus/Zoom/Iris of the camera
- **%LED Display**
- **%RS-485** multi protocols communication
- ※Power Input DC 12V



| Specification | | |
|--------------------------------------------------------------------|------------------------------------------------------------------------------------------------------|---------|
| Model No. | WS-M120B | WS-130B |
| Power Supply | | |
| Power Supply | 12VDC ±10% | |
| Power Consumption | 200mA MAX | |
| FUNCTION | | |
| P/T/Z Controller | YES | |
| Lens Controller | Zoom/Focus/Iris | |
| Control Manner | OSD Menu | |
| Joystick | 2 Axis | 3 Axis |
| Cruising Tracks | Pre-defined | |
| Communication | RS-485, PELCO-D/P Protocol(2400,4800,9600) | bps |
| Transmission | Max 1200M | |
| ENVIRONMENT | | |
| Operation Temperature | Temperature: - 10 $^{\circ}\!\!\!\!\!\!\!\!\!\!\!\!\!\!\!\!\!\!\!\!\!\!\!\!\!\!\!\!\!\!\!\!\!\!\!\!$ | |
| Storage Temperature | Temperature: - 20 $^{\circ}\!\!\!\!\!\!\!\!\!\!\!\!\!\!\!\!\!\!\!\!\!\!\!\!\!\!\!\!\!\!\!\!\!\!\!\!$ | |
| Operation Humidity | 20% - 90% RH | |
| MECHANICAL | | |
| Dimension | 130(W) X 190(H) X 64(L)mm | |
| Weight Approx | 525g | |
| *** Product specification are subject to change without notice *** | | |

www.winsafecctv.com