

2Megapixel HD IP Camera for Home



Features

- ※ 1/2.5" inch 2.0MP CMOS
- ※ 3.6MM Fix Lens;
- ※ IR View Distance:5-10m(11pcs leds);
- ※ H.264 Codet;
- ※ Plug & Play;
- ※ Video & Push;
- ※ Real- Time Frame: Rate: 15fps Max;
- ※ Power Supply 5V/2A
- ※ Onvif Compatibility;
- ※ Wifi 802.11 b/g/n

Specification

Model	WS-IP002S
Device Type	2.0 Megapixel CMOS Sensor
Size	1/2.5"
Day & Night	Yes
Min. Scene Illumination	3-8Lux(IR ON)
Infrared Sensitivity	Support
Filter	IC-CUT
IR Led	Yes
IR Distance	5-10M
Lens	
Lens	3.6MM
Focus	Fixed Lens
Aperture	Fixed Aperture
Video	
Compression	H.264
Picture Resolution	Main Flow: 1280x720@15fps 1280x720@30fps Minor Flow: 640x360@30fps
Flow Type	Support Dual Stream
Bit Rate Type	128-8192kbps
Bit Rate Type	CBR & VBR
SNR	Above 50DB
Image Enhancement	Automatic White Balance, Backlight Compensation, Brightness, Contrast, Saturation adjusted
Subtitles input	Support channel name, date/time
Flip Config	Up/Down, Left-right-flip
Audio/Alarm	
Audio	Two-way-audio
Equipment	Built-in Mic , horn
Audio IN/Out	one channel audio input, one channel audio output
Audio Compression	G.711
Alarm Way	Motion Detection: Configure motion detection area, detecting sensitivity is adjustable Cover alarm: The alarm sensitivity is adjustable
Alarm Procession	The control center to monitor, Go to PTZ preset pos, Send E-mail, Log record, SD card storage etc.
Network	
Protocol	TCP,UDP,IP,HTTP,SMTP,DHCP,DNS,DDNS,ARP,ICMP,SMTP,POP3,NTP,RTP,RTCP,Pelco-D
Ethernet Port	Ethernet(10/100 Base-T),RJ-45 conector
Security	IP Address Filter, User Password Protection, User Access Log
Software	
WEB Browser	Microsoft Internet Explorer 6.0 or above, google, firefox, etc.
Software Management	Multi-channel Network Surveillance System ONVIF Compatibility
Intelligent Software Function	Motion Detect, Miss Object Detection, Moving Object Tracking, Retrograde motion detection, etc.
Event Action	Files are stored to the back end equipment, Send E-mail, send SMS, zoom in alrm, Pop ap map, Go to PTZ preset pos etc.
Mobile Client	Iphone,Android
Remote Access	DDNS, Software, P2P
General	
Accessories	Power adapter, Network Cable, Stand, User Manual, Disk, Screw Bag
Power Consumption	DC 5V/2A
Operation Temperature	-10°C——60°C
Operation Humidity	10% -80%
Certification	CE,FCC.

※※※Product specification are subject to change without notice ※※※

www.winsafecctv.com