



WS-NVR410-10/NVR Kits 4pcs WiFi Cam + 1pcs 4CH NVR



Packing Infomration

- ※ 4CH NVR with 2pcs Antenna
- ※ 720P 1.0MP wifi IP Camera:4PCS
- ※ Power:5PCS
- ※ CD:1PCS
- ※ Mouse:1PCS
- ※ Screw package:5PC
- ※ Simple instructions:1PCS

Features

- ※ Power to the image, do not do any settings, truly fool-operation
- ※ 4CH WIFI NVR with 4 PCS WIFI IP camera, you can allow customers to follow their own according to their needs expand
- ※ Support phone operator APP
- ※ Support the post alarm, motion detection, etc.

Parameter

Model No.	WS-NVK410M-10
Video & audio input	
Network video input	4CH NVR
Video & audio output	
HDMI output	800x600, 1024x768, 1280x1024, 1440x900, 720P, 1080P
VGA output	800x600, 1024x768
Mobile phone	Support Android /Apple System
Audio output	NO
Video & audio code and decode parameters	
Record resolution	D1/HD1/CIF/720P/960P/1080P
Playback resolution	720P 100/120FPS 1080P 50/64FPS
Motion detection	Motion Detection
Synchronously playback channels	1/4CH
Record management	
Record & Snapshot mode	manual recording, regular recording, motion recording, alarm recording, events recording
Playback mode	regular playback,alarm playback,motion detection playback,events playback

Backup mode	regular backup, events backup, manual backup
Hard driver	
Mode	1*SATA
HDD capacity	each port support max 4TB HDD
External port	
Voice intercom	NO
Internet port	1PCS RJ45 10M / 100M adaptive Ethernet port
USB port	1*USB2.0
WIFI port	Built-in wireless router,With 2pcs Antenna
WIFI Distance	100M(Open area),Wall:20-30M
Network Management	
Network protocol	Built-in wireless router,With 2pcs Antenna,The image is automatically
Other	
Power supply	DC12V
Power consumption(without HDD)	≤16W
Work temperature	(-10℃--+55℃)
Work humidity	10%~90%
Case	0.8U
Size(W*L*H(cm))	280*230*57mm
Net weight(without HDD)	1.6kg
Gross weight(without HDD)	2.39kg
Color box size(L*W*H(cm))	330*320*98mm
Packing(pcs/carton)	5
Carton size (L*W*H(cm))	50*34*35cm
Gross weight(kg)	12.46kg
WIFI IP CAMERA Parameter	
Model No.	WS-IPC-410-10
Program	HI3518E+OV9712
System structure	Embedded RTOS design,Dual-Core 32-bit DSP,Pure hardware compression, watchdog;
Sensor	1/4" OV9712 CMOS sensor
Led	36PCS IR LED
Lens	4.0MM 2.0MP HD Lens
IR Distance	20-30M
Minimum illumination	Colo 0.001Lux@F1.2;
Video Processing	H.264 coding, MJPEG coding AVI format: Support Stream 0.1M~16Mbps Adjustable;
Image Frame Rate	PAL:1~25 Frame/second, NTSC:1~30 Frame/second;Adjustable
Video Streams	Main stream: 1280*720 Sub-stream: 704*576, 640*480, 352*288
Audio Processing	N/A
Network Interface	1PCS RJ45 Ethernet port, 10m / 100M Adaptive; Support WIFI,Automatic code, automatic image
WIFI Port	Support WIFI, With 1pcs Antenna
WIFI Distance	100M(Open area),Wall:20-30M
Reset Interface	N/A
TF card interface	N/A
Auto Iris Interface	N/A
Signal Interface	Support photoresistor input signal and the IR-CUT, infrared light linkage;
POE	N/A
Phone monitoring	N/A
Lightning Protection	Power, network, POE comprehensive lightning,In line with national standards GB / T17626.5, International standard IEC61000-4-5.
Working environment	(-10℃--+60℃)
Power supply	DC12V power input (12V/1A)
Weight	0.5KG
***Product specification are subject to change without notice ***	