




Binocular face recognition live detection camera WS-DB33



Features

- ※ 1/3" Progressive Scan CMOS Sensor
- ※ Effective pixels 300+300 million pixels, 30 frames @2048*1536
- ※ Supports face detection; Applied to ATM, VTM, Self-service Terminals etc.
- ※ USB video output, auto exposure, auto white balance, operating temperature range from -10°C to 60°C
- ※ Provide development kit to support secondary development
- ※ USB power

Technical Specification

Model	WS-DB33
Image Sensor	1/3" CMOS Sensor
Effective Pixels	3+3Mega pixel 2048x1536
Video System	PAL/NTSC
Min. Illumination	0.01Lux
S/N Ratio	More than 50dB
Electric Shutter	Auto
Gamma	0.45
WDR	80dB
Gain Control	OFF/AGC
Synchronization	INT
Video Output	USB Video Device
White Balance	Auto
Day & Night	Color to B&W
Lens	3.5mm
Power Supply	Powered by USB
Working Current	≤160mA
Working Temp.	-10°C—60°C
Housing Material	Aluminium Alloy
Working Humidity	0% -85% RH
Dimension	W31.8xL40xH22.8mm
Weight	50g

※※※ Product specification are subject to change without notice ※※※

www.winsafecctv.com