



UHV-100-U2-4K is a high quality 4K auto focus webcam. Only one USB(Type-C) cable is used to enable power, control and video. Thanks to being equipped with advanced image processing solution and sensor, it presents realistic color, sharp and smooth image.

UHV-100-U2-4K is developed with our own-developing focusing algorithm, to make the focus unrivalled fast and accurate. Built-in top-rated quality microphone, it can pick up the voice crystal-clearly.

UHV-100-U2-4K is the ideal for desktop video conferencing and live steaming.

Features


- Adopt the most advanced 4K image processing solution, Sony 1/2.8" 12MP UHD CMOS sensor and high-quality 80° diagonal view angle optical glass lens to output 4K30 UHD and 1080p60 FHD image
- Support digital zoom(2x at 1080P and 3x at 720P)
- * Support phase detection auto focus technology to enable focus at very short distance fast and accurate
- * Support both Landscapte and Portrait video display, flexible to meet different application
- * Compatible with Windows, Mac, Android, Linux and Google Chrome operating systems
- * Support UVC and UAC protocols and compatible with most audio and video conferencing software
- ※ Plug and play, and driver-free
- * Firmware upgrade via USB interface, easy and fast
- ** Built-in high-quality microphone, to pick up the voice clearly
- * LED indicator will light up when the machine is running and there is image output, to indicate the machine running status
- $\ensuremath{\mathbb{X}}$ Image parameters such as brightness, contrast, hue, saturation, sharpness, gamma, and white balance can be adjusted
- * With silicone lens cover to protect your privacy.

Technical Specification

| Model No. | UHV-100-U2-4K |
|-----------------------------|--|
| Image Sensor | 1/2.8" 12MP UHD CMOS sensor |
| Lens | Iris: F1.8; View Angle: 80°(Diagonal), 65°(Horizontal); Object Distance: 10cm - infinity |
| Zoom | Support digital zoom(1080P supports 2x digital zoom, 720p supports 3x digital zoom) |
| EPTZ | Support |
| Output Interface | USB(Type-C) |
| | YUY2: 1280 x 720@10, 1024 x 576@20; 640 x 480@30 |
| Video Format USB(Type-C) | MJPG: Landscape video: 3840 x 2160@30; 2560 x 1440@30; 1920 x 1080@30; 1280 x 720@30; 1024 x 576@30; 640 x 480@30 Portrait video: 1080 x 1920@30; 720 x 1280@30; 576 x 1024@30; 360 x 480@30 |
| Focus | PDAF(Phase Detection Auto Focus) |
| White Balance | Auto / Manual |
| Exposure | Auto / Manual |
| Flicker | 50HZ/60HZ/OFF |
| 2D 3d Noise Reduction | Support |
| WDR | Support |

| Backlight Compensation | Support |
|------------------------|--|
| Mirror, Flip | Support |
| Microphone Pointing | Omnidirectional microphone |
| Sensitivity | -26±2dB RL=2.2KΩ Vs=2.0V |
| S/N Ratio | 64dB |
| Polar distance | 3 - 5m |
| Input Voltage | USB Power supply |
| Working Environment | Temperature: -10°C - 50°; Humidity:≤80% |
| Webcam size | 76mm×φ48mm |
| Package size | 114.5mm x 87mm x 85mm |
| Net Weight | 0.13kg |
| Gross Weight | 0.3kg |
| Avalilable Color | Dark gray, Sliver |
| Accessories | 1.5m USB2.0(A-C) cable, Manual, Warranty card. |

Dimensional Drawing



*** Product specification are subject to change without notice ***