



Omni-directional microphone with 2 Expansion microphones WS-AM6-T



Advantages

With USB-powered, WS-AM6-T captures clear audio in a full 360 degree that widely used in the meeting room . QQ, Skype and othe VoIP call supported. And the pickup range can up to 5M + 3M and 90 db volumn output. It is compatible with Windows, Vista and Mac systems through simple plug-and-play connectivity without needing to download any drivers.

Feature

- ※ 5+3M Radios
- ※ 90 dB Speaker
- ※ High Sensitivity Omnidirectional
- ※ USB interface –PC
- ※ Auto Adjust echo cancellation
- ※ Auto Adjust human voice tracking

Function

- ※ Microphone acquisition distance of 8 meters, suitable for 40 square meters, 20 people less than the meeting room.
- ※ Support two-way expansion of the microphone, the collection distance of 8 meters, suitable for 20-60 square meters conference room, 15 people live meeting.
- ※ Support USB, is a video conferencing system, multimedia communication systems, UC unified communications platform, VPN platform voice matching. Support IN/OUT LINE analog audio signal input and output .
- ※ Through a 3.5mm connect the phone through the mobile network hands-free support external audio equipment such as mixer or external microphone system, local site amplification and enhance the effect of the microphone.
- ※ Speaker volume reached 90dB, 12 level speaker volume digital control Hands-free, mute, maintain, volume adjustment and other functions

Technical Specification

Model No.	WS-AM6-T
Interface	USB2.0 Full speed interface,3.5mm audio input/output interface, DC power interface,RJ-11 interface
Max. Power	5W
Power Supply	DC Power Adapter Supply(12V/500mA)
Radio Interference	VCCI Level B
Operating Environment	Temp.:0°C - 40°C, Humidity: 20 - 85%(no frost)
Size	Product: 350mm x 350mm x 55mm(L x W x H) / 405mm x 350mm x 130mm(L x W x H)
Weight	Net: 1000g, Packing: 2160g
Computer Environment	Windows 10(64bit/32bit), Windows 8.1(64bit/32bit), Windows 8 (64bit/32bit), Windows 7(64bit/32bit), Vista SP1(32bit), Vista SP2(32bit), Windows 2000 SP4, Mac OS X 10.5(only equipped with Intel processor machine)
Accessories	USB cable(3m), Manual, Portable Bag
Audio Parameters	
Microphone	High Sensitivity omnidirectional Microphone + 2 expansion microphone
Speaker	1(mono cycle)
Volume	Max 90dB
Frequency Bandwidth	300 - 20,000Hz
Signal Processing	Adaptive echo canceller, noise reduction, 3 Alternative Mic Auto Adjustment
※※※ Product specification are subject to change without notice ※※※	