

Under current global pandemic situation, hybrid classroom becomes very popular that part of students come to physical classroom whereas part of students stay at home and join class remotely, with the help of cloud based video conferencing technology together with intelligent AI tracking cameras, teaching & learning experience could be improved dramatically.



WINSAFE, as an experienced & professional manufacturer of AI tracking cameras have now proudly released EZC5 series EPTZ lecturer tracking cameras and students locating cameras in a view to helping teachers and students benefit from using hybrid classroom solutions.



Sneak Preview of the Camera



EZC5-V3 functiones



Built-in images swithing rule to switch among tracking & full view images of the cameras based * 8MP, 1/2.8" 4K CMOS on priority, outputs excellent switched video to record or steam, free of editing work.



» Lecturer camera: 44° HFOV Student camera: 82° HFOV

Others:

- » EPTZ Technology, can output close-up and full view images simultaneously
- » Support 4 steams, which are close-up dual steams and full view dual steams

Smart Lecturer Tracking Camera LZC5-F79NV3



Track even if lecturer wears mask.



Board Writing Mode, with deep learning technology, go to board writing preset & track once board writing is detected.



Auto adjust tilt angle as per lecturer's height.



Not track student who stands up, or waves hands.



Zone tracking on: Persons move into saved preset area, cameras move to preset

Others:

- » Keep tracking if lecturer turns around or stands still for a while
- » Track lecturer only, not track other moving object.
- » Tilt Motion while tracking
- » Track with lights on / off
- » Not track moving objects on Projector

Smart Student Locating Camera SZC5-F34NV3



Detect and analyse all students in classroom




Only student who stands up is framed.

Others:

- ☑ Correctly frame student stands up from different angles
- ☑ Correctly frame student looks down or leaves seat
- V Correctly frame student relaxes or plays.
- ☑ Correctly fram all students stand up, or wear mask.

Dimensions



Optional



Accessories

Contact Us

Tel: 0086 - 755 -26007301		
Email: sales@winsafecctv.com		
Website: www.winsafecctv.com		
Add: 3F, Jinyuan B Building, No. 302, Xixiang		
Road, Bao'an, Shenzhen,518102,China.		

Technical Data

Model	LZC5-F79NV3	SZ5-F34NV3	
Camera			
Image Sensor	1/2.8" CMOS,8.46MP		
Focal Lens	7.9mm	3.4mm	
Iris	F=2.5	F=2.2	
Field of View	44° HFOV	80° HFOV	
White Balance	Auto, Manual, One Push		
Exposure Control	Auto, Manual, Shutter Priority		
DNR	2D/3D		
Video Output Format	4KP30		
SN Ratio	Above 50dB		
Image Flip	Support		
Video adjustment	Brightness, chroma, saturation, contrast and sharpness		
Intelligente Function	Lecturer Tracking	Student Locating	
Interface			
USB	1 X USB2.0		
Network	RJ45 10/100M, POE Supported		
Audio	1 X LINE IN		
USB			
UVC	Support		
Image Compression	MJPEG/H.264/H.265		
Resolution	4KP30/25, 1080P30/25, 720P30/25, 360P30/25		
Operating System	Windows 7/8/10, Mac OS, Android OS		
Network			
Protocols	HTTP/TCP/UDP/RTSP/RTMP/ONVIF		
Protocols	VISCA		
Image Compression	H.265 / H.264		
Audio Compression	AAC		
More Stream	Main stream, Sub stream, The third stream, The fourth steam		
Resolution	Max 4kP30 Main stream: 1080P30/25, 720P30/25, 360F Sub stream: 4KP30/25, 1080P30/25, 720P3 The third stream: 720P30/25, 360P30/25 The fourth stream: 1080P30/25, 720P30/25,	0/25, 360P30/25	
General			
Power	DC 12V		
Power Consumption	Below 5W		
Operating Temperature	0°C - +40°C		
Storage Temperature	-20°C - +60°C		
Dimension(W X H X D)	149mm X 76mm X 58mm		
Weight	0.42KG		